Model : KPS30 – LP/NP

Engine MSG425- Ford – 4 cylinder inline: 2.5 liter displacement
25 Continuous KW @ 1800RPM; 30KVa 120/208V 3 phase

: Digital start panel c/w diagnostics for oil pressure, coolant temp, DC volts
: Digital AC Volts, amps, cycles
: Shutdowns for low oil pressure, high coolant temp
: Propane or natural gas option
: Electronic governor
: 12VDc alternator
: Blower fan
: Air cleaner assembly
: Cooling package
***** : Extended Run Sump Approx 50 – liter**
: 2000hr between oil changes
: Oil filter change only at 1000hrs
: Low oil level shutdown
: Low coolant level shutdown

Generator
: MecCalte 208Volt 3 phase or 120/240V single phase
: AVR controlled

Completion
: Battery and cables
: battery disconnect
: serviced with oil and coolant
: Load tested
Note: regulators, piping and hose not included

Enclosure
: Sheet metal 14 gauge
: 2- access doors
: Keyed paddle latches
: Sound attenuated/Plenum
: Powder coat finish
: Approx. 70” L X44” W X 40” H

Base Skid
: Spill contained
: Forklift pockets
: Single point lifting bale
: Corner Bollards
: Approx 90” L X 44” W X 70” H (includes exhaust tip)
: Weight – 2200lbs

AC Distribution
: 100 amp panel
: 6-15amp 110V GFI duplex
: 2 – 30amp 125/250V twist lock
: 2- 50amp 125/250V twistlock 1Phase
: ** Hard Wire splitter lugs 120/208V 3ph
: Cam Lock quick connectors 120/208V 3ph
: Main breaker
: AC Electrical Inspection Label